

Nuxeo Issue Tracker

JQL Query: project in (NXP, NXCM) AND resolution = Fixed AND fixVersion = "5.8" AND ("Impact type" = "API change" OR "Upgrade notes" is not EMPTY) ORDER BY component ASC, cf[10100] DESC, key DESC

Sorted by: Component/s ascending, then Upgrade notes descending, then Key descending

1-32 of 32 as at: 31/10/13 16:26

| Key | Summary | Upgrade notes | Components |
|-----------|---|---|--------------------------------|
| NXP-12740 | Allow displaying a warning message on production servers | new runtime property "org.nuxeo.prod" must be set to "true" for the warning message to be displayed | Admin Centre Ergonomics & |
| NXP-12412 | Provide quick ways to change default-repository-config.xml for standard options | The following nuxeo.conf variables are now available: nuxeo.vcs.blocking-timeout-millis=100 nuxeo.vcs.idle-timeout-minutes=10 nuxeo.vcs.fulltext.disabled=false nuxeo.vcs.noddl=false nuxeo.vcs.idtype=varchar | Configurator |
| NXP-12435 | Remove / Migrate remaining QueryModels | Removed modules: - deprecated addon nuxeo-platform-user-dashboard-compat (relying on jbpm addon) has been removed as it relies on query models Removed extension points: - org.nuxeo.ecm.core.search.api.client.querymodel.QueryModelService - org.nuxeo.ecm.webapp.search.SearchUIConfigService - org.nuxeo.ecm.webapp.pagination.ResultsProviderService Removed services: - org.nuxeo.ecm.core.search.api.client.querymodel.QueryModelService - org.nuxeo.ecm.webapp.pagination.ResultsProviderService - org.nuxeo.ecm.webapp.search.SearchUIConfigService Removed interfaces: - org.nuxeo.ecm.core.search.api.client.querymodel.QueryModel - org.nuxeo.ecm.platform.ui.web.api.ResultsProviderFarm Removed seam components: - documentChildrenSearchFarm - documentChildrenFarm - queryModelActions - sortActions - resultsProviderCache - domainActions Removed seam context variables: - currentDocumentChildren - currentChildrenSelectModel - currentOrderedChildrenSelectModel - sectionOrderedChildrenSelectModel Removed methods: - NavigationContext: - getCurrentDocumentChildren - getCurrentDocumentChildrenPage - invalidateChildrenProvider - DocumentActions: - getChildrenSelectModel - getSectionChildrenSelectModel - checkCurrentDocAndProcessSelectRow (see DocumentListingActionsBean instead) - processSelectRow (see DocumentListingActionsBean instead) - checkCurrentDocAndProcessSelectPage (see | Content View Search / Query |

| Key | Summary | Upgrade notes | Components |
|-----------|--|--|----------------------------|
| | | <p>DocumentListingActionsBean instead)</p> <ul style="list-style-type: none"> - processSelectPage (see DocumentListingActionsBean instead) <p>- DeleteActions:</p> <ul style="list-style-type: none"> - getDeletedChildrenSelectModel - getCurrentDocumentDeletedChildrenPage - getSearchDeletedDocuments - setSearchDeletedDocuments <p>- OrderableDocumentActions</p> <ul style="list-style-type: none"> - getCurrentOrderedChildrenSelectModel - getSectionOrderedChildrenSelectModel <p>Removes features:</p> <ul style="list-style-type: none"> - classification roots display in dashboard in classification addon <p>Removed templates:</p> <ul style="list-style-type: none"> - /incl/documents_table_virtual_nav.xhtml (not added to resources-compat module) - /incl/syndication_buttons.xhtml (not added to resources-compat module) - /incl/tabs/forum_content.xhtml (added to resources-compat even if now useless) - /incl/forum_table.xhtml (added to resources-compat even if now useless) - /incl/documents_table.xhtml (added to resources-compat even if now useless) - /incl/documents_table_trash.xhtml (added to resources-compat even if now useless) - /incl/user_services.xhtml (added to resources-compat even if now useless) - /incl/user_services_galaxy.xhtml (added to resources-compat even if now useless) - /classification/dashboard_classification_roots.xhtml (added to resources-compat even if now useless) - /incl/search/search_columns.xhtml (added to resources-compat module) - /incl/documents_tables_with_popup.xhtml (added to compat) - /incl/clipboard.xhtml (added to compat) - /incl/section_clipboard.xhtml (added to compat) - /incl/sections_table.xhtml (added to compat) - /incl/syndication_buttons.xhtml (added to compat) - /incl/trash_clipboard.xhtml (added to compat) <p>The template at /layouts/layout_listing_template.xhtml has been kept for tables that do not need selection nor sort, because it's still used in different places (users/groups listings in admin center for instance).</p> | |
| NXP-12572 | Improve style of no document / no result sentences | <p>Remove the css class: clipboardEmptyMessage</p> <p>Replaced by generic css class: emptyResult</p> | Content View Ergonomy & |
| NXP-12319 | Redis base support | <p>To configure Redis, this extension point can be used:</p> <pre><extension target="org.nuxeo.ecm.core.redis.RedisService" point="configuration"> <redis disabled="false"> <prefix>nuxeo:work:</prefix> <host>localhost</host> <port>6379</port> <password>secret</password> <database>0</database> <timeout>2000</timeout> </redis> </extension></pre> | Core |

| Key | Summary | Upgrade notes | Components |
|-----------|---|---|--------------------------|
| | | <p>To use the Redis service, do:</p> <pre>RedisService redisService = Framework.getLocalService(RedisService.class);</pre> <p>This service currently provides two methods:</p> <pre>redisService.getJedisPool(); redisService.getPrefix(); // should be used as prefix for any key</pre> <p>Standard usage pattern is:</p> <pre>protected Jedis getJedis() { return redisService.getJedisPool().getResource(); } protected void closeJedis(Jedis jedis) { redisService.getJedisPool().returnResource(jedis); } protected void myMethod() throws IOException { Jedis jedis = getJedis(); try { // ... use jedis here ... // ... all keys should be prefixed with redisService.getPrefix() } finally { closeJedis(jedis); } }</pre> | |
| NXP-12930 | Improve concurrent update detection and behavior | A new <code>ConcurrentUpdateException</code> (subclass of <code>ClientException</code>) may be thrown during a <code>save()</code> when a low-level concurrency issue is detected. It is up to the application code to rollback the transaction and retry if possible. | Core, Core SQL St |
| NXP-12988 | Allow configuration of facets that are never per-document | To specify that a facet is, for search purposes, always defined on a type and never on document instances, use in <code>default-repository-config.xml</code> (or its template): <pre><indexing> <neverPerDocumentFacets> <facet>SomeFacet</facet> <facet>AnotherFacet</facet> </neverPerDocumentFacets> ... </indexing></pre> | Core SQL St Search / Que |
| NXP-11457 | Allow flexibility in assignment of properties to table columns in VCS | In the <code>default-repository-config.xml</code> it's now possible to specify where each field goes, using <code><field></code> elements inside the <code><schema></code> element. <pre><field table="tablename" column="columnname">prefixed:fieldname</field></pre> <p>The table or column can be omitted if they don't need to be changed. If specified, they must be in the same case as in the schema defining the existing table (usually lowercase). The field must be prefixed if and only if the schema is defined with a prefix.</p> <p>For instance Nuxeo has an implicit configuration equivalent to the following (which you must not repeat):</p> <pre><schema> <field table="hierarchy" column="majorversion">major_version</field></pre> | Core SQL St |

| Key | Summary | Upgrade notes | Components |
|-----------|---|--|-----------------------|
| | | <pre><field table="hierarchy" column="minorversion">minor_version</field> </schema></pre> <p>If you want to move the dublincore title to the "hierarchy" table, you can do:</p> <pre><schema> <field table="hierarchy">dc:title</field> </schema></pre> | |
| NXP-11919 | Clean img directory from nuxeo-webapp | <p>Moving to resources-compat module:</p> <pre>/img/theme_galaxy/* bg.gif cnt.bg.gif core_servers.gif fond_error.gif logo_error.gif rightsadd_bar.gif syndication_bar.gif syndication_button.gif</pre> | Ergonomy & Seam/JSF U |
| NXP-10928 | Icons > Update and clean old icons | <p>Move to nuxeo-resources-compat addon:</p> <ul style="list-style-type: none"> * arrow_down.gif * attachment.gif, attachment.png * blog_folder.png, blogpage.png, blogpage_100.png, blogsite_100.png (also availables in the webengine addon) * blue_arrow_tool.png * calendar.gif * collaboration.png * checkbox_false.gif, checkbox_true.gif * contextuallink.png, contextuallink_100.png * dashboard.gif * directories.gif * home.gif * info.gif, info.png * logout.gif * message.png * move_all_left_black.gif, move_all_right_black.gif, move_down_black.png, move_end_black.png, move_left_black.gif, move_right_black.gif, move_top_black.png, move_up_black.png * txt.png * user_go.png * webpage.png, webpage_100.png, website.png, website_100.png (also availables in the webengine addon) * bin_closed.png | Ergonomy & |
| NXP-12999 | Enable Double click shield by default | Double Click Shield is enabled by default. | Ergonomy & Seam/JSF U |
| NXP-10949 | Can't change label of default metadata view fragment on summary | All summary widget types that used to hardcode their label should be added the control "handleLabels" to true, and should define an empty label to get back the old behaviour. | Ergonomy & |
| NXP-12390 | NXP-8132 Feedback messages and Admin message should be closable | <p>'message_banner.xhtml' template has been changed to use new tag 'nxh:messages' that uses jQuery Ambiance plugin to display the Faces Messages. If you overrode the template, you need to update it to use the new tag.</p> <p>The 'h:messages' tag still work but it won't push notification to the jQuery plugin.</p> | Ergonomy & |
| NXP-12791 | Upgrade to org.osgi.core 4.2.0 | Upgrade/replace org.osgi:osgi-core:4.1 with org.osgi:org.osgi.core:4.2.0 | Infrastructure |

| Key | Summary | Upgrade notes | Components |
|-----------|--|---|----------------------------|
| NXP-12557 | Activate Jacoco only for Sonar analysis | Running a quality analysis with Sonar+Jacoco now requires activation of the Maven profile "sonar". | Installers / Au |
| NXP-12823 | Remove deprecated Nuxeo Core Client | Removed deprecated org.nuxeo.ecm.core:nuxeo-core-client | Java client |
| NXP-9343 | Detect if a SNAPSHOT package must be replaced | Return type of org.nuxeo.connect.update.standalone.PackagePersistence.getState(String) changed from int to org.nuxeo.connect.update.PackageState | Launcher |
| NXP-11992 | Update action templates to use generic actions by type | <p>actions in USER_MENU_ACTIONS or USER_SERVICES_BOTTOM must be added the type "bare_link" if they need to display a rest URL (if their link is not starting with "#{").</p> <p>category USER_SERVICES_BOTTOM is deprecated, USER_MENU_ACTIONS or USER_SERVICES should be used instead.</p> <p>actions in category SEARCH_BOX_TEMPLATE are not displayed in header anymore, use actions of type "template" in category SEARCH_ACTIONS instead.</p> <p>actions in category SEARCH_LINKS are not displayed in header anymore, use actions of type "bare_link" in category SEARCH_ACTIONS instead.</p> | Layouts / Wi Seam/JSF U |
| NXP-12824 | Remove deprecated Nuxeo Web Embedded Distribution | Removed deprecated org.nuxeo.ecm.web:nuxeo-web-embedded-distribution | Packaging, S |
| NXP-12508 | NXP-12479 Adapt user/group to pagination system | The AbstractGroupsPageProvider class is now a parametrized class. If you were extending this class, you probably need to parametrized it with DocumentModel. If you were extending GroupsPageProvider, you have nothing to change. | Rest API |
| NXP-12671 | Cleanup templates in nuxeo-platform-webapp | removed very old unused templates, no migration available for them | Seam/JSF U |
| NXP-12605 | Add access key navigation with actions | The helper for available access keys on the page is displayed when pression "MAJ+h" | Seam/JSF U |
| NXP-9384 | Allow using Ajax for tab switching | Runtime property nuxeo.jsf.useajaxTabs can be set to "true" to activate the ajaxified behaviour | Seam/JSF U |
| NXP-12566 | In bulk edit, when you edit a filed which is a select2, the check box is not automatically checked | Naturally fixed with NXP-12635 | Seam/JSF U |
| NXP-8652 | NXP-11728 Remove doc types "blog" and "website" from default platform | Blogs and Websites icons from DM are now in the addon, and are duplicated into the resource-compat module just in case. | Seam/JSF U |
| NXP-12929 | Fix typo in DocumentMetadataGroupComputerDescriptor class | Fix typo contribution item name documentMetadataGroupComuter to documentMetadataGroupComputer | Security / Rig |
| NXP-10931 | NXP-10928 Icons update > Tree | Move blue_arrow_tool.png to resources-compat | Style & CSS |
| NXP-11970 | CSS > Remove old classes | CSS class removed: .archiveTabContent .archiveTabContent .notEditable .archiveTabContent .currentDocumentInformation .taskAssign .taskActions .closedContent .relationCommentList | Style & CSS |
| NXP-12625 | Add Label generation logic in Computer Group | Add a new interface for Group Computer (GroupComputerLabelled) specifying the Group Label Management. Implementing a Group Computer with this interface will automatically improve Group produce with the label express into the getLabel Method. | User prefere |
| NXP-12749 | Fix automation module deployment when using dev mode | webengine dev mode has been removed | WebEngine |

| Key | Summary | Upgrade notes | Components |
|---------------------------|--|---|--------------------|
| NXP-12840 | Workflow task form control are not double click shielded | Workflow controls are now based on commandButton | Layouts / Workflow |
| NXP-12621 | Add possibility to clean up old workflow instances | <p>From 5.8 by default, completed workflow instances are removed. The clean-up is triggered daily at midnight. (by a scheduler with the id 'workflowInstancesCleanup' -that can be overridden to change its quartz expression).</p> <p>If you want to keep these workflows add the following line in nuxeo.conf: nuxeo.routing.disable.cleanup.workflow.instances = true</p> <p>By default the number of instances deleted every time the scheduler is trigger is set to 100.</p> <p>This can be changed by setting the property 'nuxeo.routing.cleanup.workflow.instances.batch.size' in nuxeo.conf.</p> | Workflow |